



Tech Data Sheet

Aqua Mask Overspray Maskant

PRODUCTS CPS-X1 Aqua Mask (Available in one, five, fifteen, and fifty-five gallon containers.)	
FEATURES Aqua Mask helps to ensure that you will get professional results when used on dust trap areas like engine compartments, wheel wells, grilles and door jambs by entrapping dirt and dust particles. Aqua Mask is easy to apply with any conventional spray gun and easy to wash off the water after finish has been completely dried.	
DESCRIPTION Aqua Mask is a water based, ready for use, sprayable mask that dries to a non-tacky, clear plastic film. It protects vehicle surfaces from primer, undercoating and paint overspray.	RECOMMENDED USES For bulk masking of surfaces to help protect against paint overspray only, and is not intended to protect again a direct hit of paint or primer. Never spray any protective coating on cloth tops or interiors.
PHYSICAL PROPERTIES COLOR Transparent Red SHELF LIFE One year DRY TIMES 30 min depending on temp. and humidity	SURFACE PREPARATION Remove loose dust or dirt from surface. Mask around area to be painted using at least 12" wide masking paper. After masking, fold the paper into the area being painted. Spray the balance of the vehicle with a single coat of Aqua Mask.
RECOATING Removal Procedure: Use water and sponge or pressure wash to remove.	MIXING INSTRUCTIONS Thinning is not recommended for this product.
EQUIPMENT Can be sprayed with any conventional or HVLP gun.	
APPLICATION Apply one medium wet coat. An additional coat may be applied after a five minute flash if full coverage is not achieved in the first coat. Material will dry to a transparent, tack free film. Let product dry for at least 20 minutes at 75° F and 50% relative humidity before exposing to over-spray. DO NOT use on fabric or fabric covered roofs. Spray mask will tolerate sunlight for short periods of time. Excessive sunlight may cause difficulty at clean-up time, more so on poorly maintained finishes.	
CLEAN UP Allow Aqua Mask to remain until paint is completely dry, per paint manufactures' instructions or until any buffing or compound is complete. Water rinse or peel off dried film. This is a water-based product, so clean up tools and equipment with soap and water.	
CAUTIONS Avoid skin contact, use protective equipment when spraying. Avoid inhaling spray mist. Spills or overspray should be rinsed with water to avoid slipping. FIRST AID: EYE CONTACT: Flush eyes with water. If irritation persists, consult a physician. SKIN CONTACT: Wash with soap and water. If irritation persists, consult a physician. INGESTION: Do not induce vomiting. Drink 2-3 glasses of water. Consult a physician.	
WARRANTY CPS Coatings guarantees the standard quality of this product and its adherence to our specifications. However, as the use of this product is beyond our control, we expressly disclaim responsibility for its handling, storage, use, results obtained or any injury or special indirect or consequential damage of any nature whatsoever.	