



Tech Data Sheet

CPS-6300 Peelable Booth Coating

FEATURES									
CPS Coatings Peelable Booth Coating is an elasticized latex product for use on the walls and ceilings in automotive and industrial paint booths. It has a non-glare finish that will help reduce shadows for truer color retention. Keeps walls and ceilings of paint booth looking new.									
<p style="text-align: center;">DESCRIPTION</p> <p>Cover is approximately 100 sq. ft. per gallon at recommended 8 mils. Three to four mils per coat with airless sprayer is ideal. <u>Must have a dry film thickness of five mils minimum (Recommended six to eight mils).</u></p>	<p style="text-align: center;">RECOMMENDED USES</p> <p>Peelable Booth Coating is designed to protect paint booth walls, lights, etc. from paint and overspray.</p>								
<p style="text-align: center;">PHYSICAL PROPERTIES</p> <table border="0"> <tr> <td>GENERIC TYPE</td> <td>Elasticized Latex</td> </tr> <tr> <td>COLOR</td> <td>White</td> </tr> <tr> <td>SHELF LIFE</td> <td>One year</td> </tr> <tr> <td>COVERAGE</td> <td>739 sq.ft. per gal. at 1 mil (theoretical coverage)</td> </tr> </table>	GENERIC TYPE	Elasticized Latex	COLOR	White	SHELF LIFE	One year	COVERAGE	739 sq.ft. per gal. at 1 mil (theoretical coverage)	<p style="text-align: center;">SURFACE PREPARATION</p> <p>Clean or refinish booth walls prior to applying. Surfaces should be completely dry before applying product.</p>
GENERIC TYPE	Elasticized Latex								
COLOR	White								
SHELF LIFE	One year								
COVERAGE	739 sq.ft. per gal. at 1 mil (theoretical coverage)								
<p style="text-align: center;">RECOATING</p> <p>Removal Procedure: When used in an un-heated booth, check for ease of removal in four (4) months. If the coating is still stable it may be recoated rather than removed. The thinner the film the harder to peel. Peels best after five to six coats.</p>	<p style="text-align: center;">MIXING INSTRUCTIONS</p> <p>Thinning not recommended, but if necessary <u>NO more than 5% with water.</u></p>								
<p style="text-align: center;">EQUIPMENT</p> <p>Can be applied using conventional spray equipment.</p>									
APPLICATION									
Can be sprayed, brushed or rolled, but airless spray is the ideal method of application. Conventional spray is possible with a very large fluid needle. First application: minimum 2-3 coats. Do not use in heated spray booths exceeding 150°F. Substrate must be clean, smooth and non-porous for proper adhesion.									
CLEAN UP									
This is a latex product, so clean up tools and equipment with soap and water. For disposal, follow your federal and state regulations for latex paint disposal.									
CAUTIONS									
<p>CONTENTS ARE FLAMMABLE LIQUID Vapors may cause flash fires. Keep away from heat, sparks, and open flame. During use and until all vapors are gone. Keep area ventilated - Do not smoke - Extinguish all flames, pilot lights, and heaters - Turn off stoves, electric tools and appliances, and any other sources of ignition. VAPOR HARMFUL Use only with adequate ventilation. Wear an appropriate properly fitted vapor/particle respirator (NIOSH/OSHA approved) during and after application. Follow respirator manufacturer's directions for respirator use. Avoid contact with eyes and skin. Wash hands after using. Keep container closed when not in use. Do not transfer contents to other containers for storage. FIRST AID: IF INHALED: If affected, remove from exposure. Restore breathing, keep warm and quiet. IF ON SKIN: Wash affected area thoroughly with soap and water. Remove contaminated clothing. Launder before re-use. IF IN EYES: Flush eyes with large amounts of water for 15 min. Get medical attention. IF SWALLOWED: Get medical attention immediately. SPILL AND WASTE: Remove all sources of ignition. Ventilate and remove with inert absorbent. Incinerate in approved facility. Do not incinerate closed container. Dispose of in accordance with Federal, State and Local regulation regarding pollution. DELAYED EFFECTS FROM LONG TERM OVEREXPOSURE: Contains solvents which can cause permanent brain damage and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents can be harmful or fatal. DO NOT TAKE INTERNALLY - KEEP OUT OF REACH OF CHILDREN</p>									
WARRANTY									
CPS Coatings guarantees the standard quality of this product and its adherence to our specifications. However, as the use of this product is beyond our control, we expressly disclaim responsibility for its handling, storage, use, results obtained or any injury or special indirect or consequential damage of any nature whatsoever.									