



# CPS COATINGS, INC. TECHNICAL DATA

## TBL6-A / TBL-A (Armour Liner) Truck Bedliner

<b>Generic Type</b>	Acrylic Urethane
<b>Description</b>	2 component polyurethane. Designed to be resistant to impact, scratching chemicals, salt water, UV lighting, also to improve overall appearance of truckbeds.
<b>Color</b>	Black or tintable clear base available
<b>Solids Content</b>	65% by volume
<b>Shelf Life</b>	1 Year unmixed
<b>Coverage Thickness</b>	80 to 90 sq.ft. Per kit at 20 mil Recommended 15 - 20 mils DFT
<b>Dry Time</b>	10 - 15 min - Tack Free 2 - 4 hours – Can Be Delivered 48 hours – Full Cure Pot Life – 50-55 min. @ 90 deg.F
<b>Solvent</b>	Up To 5% Lacquer Thinner - Only If Needed
<b>Recommended Uses</b>	<u><i>Armour Liner</i></u> is recommended for truck beds, boats, transport trailers, sewage plants, offshore drilling platforms and equipment, deerstands, and much more.
<b>Surface Preparation</b>	Refer to the instruction sheet with kit or contact your representative.
<b>Application</b>	Air Spray: Schutz type gun @ 60 – 80 PSI.
<b>Pot Life</b>	50 min. to 1 Hour